

**AMENDMENTS TO THE CLAIMS**

Please cancel claims 1-19. Please add new claims 20-37. Following is a complete listing of the claims pending in the application.

1-19. (Cancelled)

20. (New) A combination picture-taking and sound-generating apparatus for use with a portable electronic device, the apparatus comprising:

- a housing having a generally circular cross-section, an open end, a closed end, exterior walls defining an exterior surface, at least one audio port in the exterior surface, a viewfinder window in the exterior surface, and interior walls defining a generally hollow interior portion;
- a sound-generating element within the generally hollow interior portion and proximate to the at least one audio port, wherein the sound-generating element is configured to receive audio signals from the portable electronic device and generate sounds corresponding to the audio signals;
- a picture-taking element within the generally hollow interior portion and proximate to the viewfinder window, wherein the picture-taking element is configured to capture images and generate image signals corresponding to the captured images for transmission to the portable electronic device; and
- a cap covering the open end of the housing, wherein the cap and the housing enclose the sound-generating element and the picture-taking element, and wherein the generally hollow interior portion is positioned as a resonant space for sounds generated by the sound-generating element.

21. (New) The apparatus of claim 20 wherein the closed end has a first axle formed thereon and the cap has a second axle formed thereon, the first and second axles configured to be operably coupled to the portable electronic device, and wherein

the apparatus is rotatably movable about the first and second axes relative to the portable electronic device.

22. (New) The apparatus of claim 20 wherein the at least one audio port is at a portion of the exterior surface corresponding to the closed end.

23. (New) The apparatus of claim 20 wherein the picture-taking element includes one of a Charge Coupled Device (CCD) and a Complementary Metal-Oxide Semiconductor (CMOS).

24. (New) The apparatus of claim 20 wherein the sound-generating element includes a Mylar speaker.

25. (New) An apparatus for use with a portable electronic device, the apparatus comprising:

- a body having an exterior surface, at least one audio port in the exterior surface, an opening in the exterior surface, and an interior region;
- at least one sound-generating element in the interior region and proximate to the at least one audio port, wherein the at least one sound-generating element is configured to be operably coupled to the portable electronic device; and
- at least one image-capturing element in the interior region and proximate to the opening, wherein the at least one image-capturing element is configured to be operably coupled to the portable electronic device,

wherein the body encloses the at least one sound-generating element and the at least one image-capturing element, and wherein the interior region of the body provides a resonant space for sound generated by the at least one sound-generating element.

26. (New) The apparatus of claim 25 wherein the body has a generally cylindrical shape having a first closed end and a second closed end, and wherein the apparatus further comprises:

- a first axle at the first end; and
- a second axle at the second end, the first and second axles configured to be operably coupled to the portable electronic device, and wherein the apparatus is rotatably movable about the first and second axles relative to the portable electronic device.

27. (New) The apparatus of claim 25 wherein the apparatus is configured to be fixedly positioned in the portable electronic device.

28. (New) The apparatus of claim 25 wherein the body includes:

- a first portion having an interior region; and
- a second portion configured to be attached to the first portion, the first and second portions forming the interior region of the body that provides the resonant space.

29. (New) An apparatus for use with a portable electronic device, the apparatus comprising:

- a housing having exterior walls defining an exterior surface, a first audio port in the exterior surface, a second audio port in the exterior surface, an opening in the exterior surface, a first set of interior walls defining a first chamber, and a second set of interior walls defining a second chamber;
- a first sound-generating element in the first chamber and positioned toward the first audio port, wherein the first sound-generating element is configured to be electrically connected to the portable electronic device;
- a second sound-generating element in the second chamber and positioned toward the second audio port, wherein the second sound-generating

element is configured to be electrically connected to the portable electronic device; and  
an image-capturing element positioned toward the opening, wherein the image-capturing element is configured to be electrically connected to the portable electronic device,  
wherein the first chamber substantially encloses the first sound-generating element, thereby forming a first resonant space for first sounds generated by the first sound-generating element, and wherein the second chamber substantially encloses the second sound-generating element, thereby forming a second resonant space for second sounds generated by the second sound-generating element.

30. (New) The apparatus of claim 29 wherein the housing is configured to be fixedly positioned in the portable electronic device.

31. (New) The apparatus of claim 29 wherein the housing has a generally cylindrical shape having a first closed end and a second closed end, and wherein the apparatus further comprises:

a first axle at the first end; and  
a second axle at the second end, the first and second axles configured to be operably coupled to the portable electronic device, and wherein the apparatus is rotatably movable about the first and second axles relative to the portable electronic device.

32. (New) The apparatus of claim 31 wherein the opening is a first opening, the housing further has a second opening in the exterior surface, and further comprising an electrical connector attached to the image-capturing element, wherein the electrical connector passes through the second opening and extends around the exterior surface so as to enable rotation of the apparatus in the portable electronic device.

33. (New) The apparatus of claim 32 wherein the electrical connector is attached to the first and second sound-generating elements.

34. (New) The apparatus of claim 29, wherein the housing includes:  
a first portion;  
a first generally concave portion configured to be attached to the first portion to form at least one of the interior walls of the first set that define the first chamber; and  
a second generally concave portion configured to be attached to the first portion to form at least one of the interior walls of the second set that define the second chamber.

35. (New) The apparatus of claim 34 wherein the first audio port is located in a first portion of the exterior surface corresponding to the first generally concave portion and the second audio port is located in a second portion of the exterior surface corresponding to the second generally concave portion.

36. (New) An apparatus for use with a portable electronic device, the apparatus comprising:

sound-generating means for generating sound, wherein the sound-generating means are configured to be electrically connected to the portable electronic device;

image-capturing means for capturing images, wherein the image-capturing means are configured to be electrically connected to the portable electronic device; and

housing means for housing the sound-generating means and the image-capturing means in an enclosed space that functions as a resonant space for the sound generated by the sound-generating means.

37. (New) The apparatus of claim 36, further comprising means for enabling the apparatus to be rotatably positioned in the portable electronic device.